

**YUG 7202**

**>General information**

Colour	colourless
Gloss level 60° (Gloss)	-
Form of delivery	fluid
Product type	Primer
Order number	YUG 7202
Function	UV lacquers, clear - primers

**>Others**

Shelf life in weeks	26
Storage temperature	5 - 25 °C
conditions of transport	frost-free - up to a maximum of 35 °C
Working Temperature Range	20 - 40 °C

**>Areas of application**

Substrate material	Dark deciduous woods with fine pores, Light deciduous woods with fine pores, Light deciduous woods with coarse pores
--------------------	--

**>Mixing information**

Equipment cleaner	UV 7100
-------------------	---------

**>Application**

Total application volume	60 g/m <sup>2</sup>
Application	Putty roller
Number of coats (max)	2
Amount per layer (minimum)	10 g/m <sup>2</sup>
Amount per layer (max)	30 g/m <sup>2</sup>

**>physical/chemical data**

Flow time / Viscosity (+/- 15 %)	100 s / DIN 53211 - 8 mm
Density	1,12 kg/l
Flashpoint	> 60 °C
Non-volatile proportion	96 %
VOC EU %	4 %
VOC FR	C

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at [www.hesse-lignal.de](http://www.hesse-lignal.de) or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Safety data sheet is provided in accordance with EC regulation no. 1907/2006.