

**YUU 76204**

**>General information**

Colour	colourless
Gloss level 60° (Gloss)	18 - 23
Gloss level designation	silk matt
Form of delivery	fluid
Product type	Finishing lacquer
Order number	YUU 76204
Function	UV lacquers, clear – spray coatings containing solvents

**>Others**

Shelf life in weeks	26
Storage temperature	15 - 40 °C
conditions of transport	frost-free - up to a maximum of 35 °C
Working Temperature Range	20 - 40 °C

**>Areas of application**

Substrate material	suitably pre-primed
--------------------	---------------------

**>Mixing information**

Equipment cleaner	UV 7100
-------------------	---------

**>Application**

Total application volume	100 g/m <sup>2</sup>
Application	Air mix
Number of coats (max)	1
Amount per layer (minimum)	80 g/m <sup>2</sup>
Amount per layer (max)	100 g/m <sup>2</sup>

**>physical/chemical data**

Flow time / Viscosity (+/- 15 %)	50 s / DIN EN ISO 2431 - 4 mm
Density	0,97 kg/l
Flashpoint	23 °C
Non-volatile proportion	36 %
VOC EU %	64 %
VOC FR	C

Our technical information is continually adapted to keep up to date with the latest technology and statutory regulations. The indicated values are no specification, but typical product data. The latest version is always available online at [www.hesse-lignal.de](http://www.hesse-lignal.de) or talk to your local account manager. This information is for advice and is based on the best knowledge available and careful research in line with the current state of the art. This information cannot be held as legally binding. We also refer you to our terms and conditions of business. Safety data sheet is provided in accordance with EC regulation no. 1907/2006.